



Integrated Systems

By integrating the trusted features of Schmidt Aftercoolers and Schmidt blast equipment, these units increase your profitability and efficiency by removing moisture from air, while minimizing pressure drop and equipment footprint on jobsite. Extremely positive feedback has been received on these units and with multiple sizes and options available, these integrated systems are sure to be seen on many more job sites in the future!

FEATURES

- Virtually any size or option can be customized to fit specific project needs
- Minimizes equipment footprint on the job site
- Reduces air hose in project area
- Reduces pressure loss by minimizing air hose length
- Extremely low pressure loss for increased productivity
- Optional carriage wheels for easy maneuvering
- Drier air and media = save time and money
- Trusted Schmidt valves and controls



Integrated AmphiBlast
(Front)



Integrated AmphiBlast
(Back)



Integrated Systems



FEATURES

- Design effectively treats blast air only
- Modular reclaimer design gives the ability to change from standard cyclonic to optional airwash separator
- Re-designed dust collector helps extend life and allows easy access to filters
- Additional vacuum hose port for cleaning hopper screen
- Re-designed handle for easier steering
- Abrasive indicator for quick and easy media level viewing
- Dust collector is HEPA compatible for lead abatement projects



**3.5 cu ft BRS x 250 cfm
Aftercooler**



**6.5 cu ft Blaster x 400 cfm
Aftercooler**



© 2026 Schmidt. All rights reserved. Scan the QR code for product, patent, trademark, and legal information.

Contact your local Schmidt distributor or call Schmidt below for distributor information.



US: 1-800-231-2085
Asia: +603-7865 6524
Middle East: +966-54-500-8808



schmidtmfg.com